



## TRAIL

### RAZE

Gloss Black / Dirty White

<b>FRAME</b>	Raze 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 130mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05
<b>SIZES</b>	S: 380mm / M: 420mm / L: 470mm / XL: 510mm
<b>REAR SHOCK</b>	Fox Float DPS LV EVOL Performance, 205x57.5mm. Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	Light compression, light rebound, air volume spacer 0.6
<b>FORK</b>	RockShox 35 Gold 29 RL, 150mm, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
<b>HEADSET</b>	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
<b>STEM</b>	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
<b>GRIPS</b>	Onoff Twin, 1lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
<b>SADDLE</b>	MDK series PU 2023
<b>FRONT BRAKE</b>	Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
<b>REAR BRAKE</b>	Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
<b>BRAKE LEVER</b>	Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
<b>RIMS</b>	MDK-EPI 29, 30mm internal width, tubeless ready, 32 spokes
<b>SPOKES</b>	CN round stainless steel
<b>FRONT HUB</b>	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

<b>REAR HUB</b>	Formula DHT148 Boost 12x148mm, sealed bearings, IS 6 bolts
<b>FRONT TIRE</b>	Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
<b>CRANKSET</b>	Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm
<b>RINGS</b>	32T, steel, X-Sync 2
<b>BOTTOM BRACKET</b>	Sram DUB BSA, sealed bearings, 73mm
<b>PEDALS</b>	---
<b>CHAIN</b>	Sram SX Eagle, 12s, Powerlock
<b>FRONT DERRAILLEUR</b>	---
<b>REAR DERRAILLEUR</b>	Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
<b>SHIFT LEVERS</b>	Sram Trigger SX Eagle, 12s, X-Actuation 1:1
<b>CASSETTE</b>	Sram PG-1210, 11-50T, 12s
<b>DERAILLEUR HANGER</b>	Sram UDH
<b>OTHERS</b>	---
<b>WEIGHT</b>	---