



## ENDURO

### FOXY

Matte Black / Nimbus Grey / Flame Red

<b>FRAME</b>	Foxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 150mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05
<b>SIZES</b>	S: 380mm / M: 420mm / L: 470mm / XL: 510mm
<b>REAR SHOCK</b>	Fox Float DPS LV EVOL Performance, 205x62.5mm. Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 22.2x10mm bottom bushings
<b>SHOCK SETTINGS</b>	Light compression, light rebound, air volume spacer 0.6
<b>FORK</b>	Fox 36 29 Float GRIP EVOL Rhythm, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: sweep adjust compression, low-speed rebound, air preload
<b>HEADSET</b>	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
<b>STEM</b>	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
<b>GRIPS</b>	Onoff Twin, 1lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
<b>SADDLE</b>	SDG BEL-AIR 3.0, LPU foam, steel rails
<b>FRONT BRAKE</b>	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
<b>REAR BRAKE</b>	Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads
<b>BRAKE LEVER</b>	Sram G2 R, tool-free reach adjust
<b>RIMS</b>	e*thirteen LG1 Enduro, IW30 Hookless, 6069 Welded Aluminum, 30mm internal width, tubeless ready, 28 spokes
<b>SPOKES</b>	e*thirteen custom Hive triple-buttet black steel, alloy nipples, nipple washers
<b>FRONT HUB</b>	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts

<b>REAR HUB</b>	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, Shimano freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
<b>CRANKSET</b>	Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm
<b>RINGS</b>	32T, steel, X-Sync 2
<b>BOTTOM BRACKET</b>	Sram DUB BSA, sealed bearings, 73mm
<b>PEDALS</b>	---
<b>CHAIN</b>	Sram SX Eagle, 12s, Powerlock
<b>FRONT DERRAILLEUR</b>	---
<b>REAR DERRAILLEUR</b>	Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
<b>SHIFT LEVERS</b>	Sram Trigger SX Eagle, 12s, X-Actuation 1:1
<b>CASSETTE</b>	Sram PG-1210, 11-50T, 12s
<b>DERAILLEUR HANGER</b>	Mondraker M068
<b>OTHERS</b>	---
<b>WEIGHT</b>	---